

08.10.2019 – 14:03 Uhr

Brenntag and Centroplast present POM CentroGlide, a new material boasting excellent sliding and non-stick properties, and fully conformant with food safety regulations

Dear all,

Please find attached the press release of Brenntag on the launch of POM CentroGlide, a new material boasting excellent sliding and non-stick properties, realised jointly with Centroplast.

For further information please see the press release below.

If you have any questions, please do not hesitate to contact us.

Best regards,

Hubertus Spethmann

Essen, October 8, 2019

Brenntag and Centroplast present POM CentroGlide, a new material boasting excellent sliding and non-stick properties, and fully conformant with food safety regulations

Brenntag, the global market leader in chemical and ingredients distribution and a leading developer of compounds, has joined forces with Centroplast to launch an innovative semi-finished product. Thanks to its engineering, POM CentroGlide offers excellent sliding and non-stick properties, and is fully conformant with food safety regulations.

It moreover combines good wear and abrasion properties with very low adhesive and adhesion properties – features that are fundamentally disparate and that, offered together in this way, boast significant benefits both in terms of cost and product quality.

Brenntag Polymers develops individual material solutions by applying a user-oriented approach, and in working together with Centroplast has created this tribologically optimised material on the basis of customer-specific requirements.

By preventing materials from adhering to manufacturing components, POM CentroGlide minimizes the mechanical strain on various production parts. This reduces friction and wear and, as such, increases the service life and capacity of technical manufacturing systems. It also allows for work processes and downtimes to be optimised. The resulting longer intervals between cleaning and parts-replacement processes in turn significantly reduce costs for maintenance and spare parts. POM CentroGlide's non-stick features are inherent in the product's composition, meaning that there is no need for any additional non-stick coatings.

The product's food-grade conformity extends its already broad profile of features. CentroGlide is especially effective when it comes to food production processes involving pasty substances such as cake mix, as such substances often stick to the corresponding embossing rollers, moulds or cylinders.

In a trial, the new food-grade POM CentroGlide displayed a 30% lower coefficient of friction than the standard food-grade POM Copo, indicating that it has excellent sliding properties. Moreover, observing the friction of the two POM types over time showed a clear difference between them: while the coefficient of friction increased sharply and continually in the standard POM, it maintained a much better level in the CentroGlide product.

CentroGlide therefore offers a better coefficient of friction and responds positively to sticky substances and adhesives. A 90° peel-off test conducted on a well-known adhesive strip (on Centroplast POM plates compliant with DIN-ISO 29862:2018) clearly showed that, when POM CentroGlide is used, the adhesive strip could be detached from the POM test specimen using half the load over the same distance. This functionality is particularly useful in applications within the adhesives processing industry.

It moreover sets CentroGlide apart from PTFE as a non-stick material, especially where complex components such as injection moulding applications are concerned. The combination of POM properties (high strength, rigidity, toughness, excellent machinability, high dimensional stability, outstanding resilience, etc.) and specific CentroGlide features makes the new material an excellent alternative to the more expensive PTFE.

For more information on Brenntag Polymers, go to <https://www.brenntag.com/germany/en/solutions/industries/material-science/polymers/products/index.jsp>

For more information on POM CentroGlide, go to <https://www.centroplast.com/>

About Brenntag Polymers:

Brenntag Polymers develops, produces and markets compounds in engineering plastics and high-performance polymers and is a product development partner for customer-specific material solutions. In addition to our distribution range for products from other

leading manufacturers and brands, our customers also have some 700 products at their disposal that we have developed ourselves. Our support extends from product development, via application and processing consultancy, right through to readiness for the market. Working in close cooperation with our customers, we develop individual materials that are precisely tailored to their subsequent use. We have specialist know-how in the fields of metal substitution, thermally conductive compounds, drinking water and food-compatible compounds, and detectable and tribologically optimised compounds. Our plastics are individually adjustable and have proved successful for numerous applications in a wide range of sectors, including the automotive and E&E segments, lighting applications, architecture, building and construction, sport and leisure, industry, medicine, etc.

Contact:

Frank Dahlke

Business Manager

Polymers, DACH region

frank.dahlke@brenntag.de

About Brenntag GmbH:

Brenntag GmbH is the German subsidiary of the Brenntag Group, the global market leader in chemicals and ingredients distribution. The company employs around 1,200 at 16 locations in Germany, providing both all-in solutions and individual chemical products. Our range of products and services includes more than 10,000 industrial and specialty chemicals as well as numerous services, such as just-in-time deliveries, mixes and formulations, repackaging, inventory management and application technology.

Press contact:

Hubertus Spethmann

Brenntag AG

Corporate Communications

Messeallee 11

45131 Essen

Germany

Telephone: +49 (201) 6496-1732

E-Mail: hubertus.spethmann@brenntag.de

<https://www.brenntag.com>

Diese Meldung kann unter <https://www.presseportal.de/en/pm/108645/4395613> abgerufen werden.